

Hand hydraulic crimping tool

**HCT-185**

1. Crimping head rotates 360°
2. Two stage hydraulic, automatic pressure release
3. Super quick, light, durable
4. Flip top style for easy access to the fitting



**HCT-6022**

1. Crimping head rotates 360°
2. Two stage hydraulic, automatic pressure release
3. Super quick, light, durable
4. Flip top style for easy access to the fitting



**HCT-12042**

1. Crimping head rotates 360°
2. Two stage hydraulic, automatic pressure release
3. C-head with 42mm opening width for easy access to the fitting
4. Suitable for crimping cable terminal, C-clamp, connector and overhead line



**EP-431**

1. Crimping head rotates 180° , suitable for various working angles
2. Two stage hydraulics, automatic pressure release
3. C-shaped opening jaw design



**EP-510C**

1. Crimping head rotates 180° , suitable for various working angles
2. Two stage hydraulics, automatic pressure release
3. C-shaped opening jaw design



	HCT-185	HCT-6022	HCT-12042	EP-431	EP-510C
Crimping Force	5t	6t	12t	12t	13t
Stroke	15mm	17mm	42mm	31mm	38mm
Rated Pressure	700bar	700bar	700bar	700bar	700bar
Crimping Capacity	Max. 185mm <sup>2</sup>	Max. 300mm <sup>2</sup>	Max. 400mm <sup>2</sup>	Max. 300mm <sup>2</sup>	Max. 400mm <sup>2</sup>
Net Weight	2kg	3.8kg	6.1kg	6.2kg	7.8kg
Standard Dies	Cu10-185mm <sup>2</sup>	Cu50-300mm <sup>2</sup>	Cu70-400mm <sup>2</sup>	Cu50-300 mm <sup>2</sup>	Cu70-400 mm <sup>2</sup>
Dimensions	37*13*6cm	50*17*7cm	56*17*7cm	67*17*9cm	67*17*9cm
PP Plastic case	51*22*11cm	51*22*11cm	51*22*11cm	51*22*11cm	51*22*11cm

Hand hydraulic crimping tool

**BQK-70**

1. Crimping head rotates 180°
2. High-density clamp head, stronger pressure
3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm
4. C-shaped opening jaw design



**BQK-120**

1. Crimping head rotates 180°
2. High-density clamp head, stronger pressure
3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



**BQK-240**

1. Crimping head rotates 180°
2. High-density clamp head, stronger pressure
3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



**BQK-300**

1. Crimping head rotates 180°
2. High-density clamp head, stronger pressure
3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



**HCT-6030**

Dieless hand hydraulic crimping tools

1. Crimping head rotates 180° , suitable for all working angles
2. Two stage hydraulics, automatic pressure release
3. C-shaped opening jaw design



	BQK-70	BQK-120	BQK-240	BQK-300	HCT-6030
Crimping Force	6t	8t	12t	13t	6t
Stroke	12mm	16mm	20mm	20mm	32mm
Rated Pressure	700bar	700bar	700bar	700bar	700bar
Crimping Capacity	Max. 70mm <sup>2</sup>	Max.120mm <sup>2</sup>	Max.240mm <sup>2</sup>	Max.300mm <sup>2</sup>	Max. 300mm <sup>2</sup>
Net Weight	3kg	4.5kg	6.8kg	6.6kg	4.8kg
Standard Dies	Cu4-70mm <sup>2</sup>	Cu10-120mm <sup>2</sup>	Cu16-240mm <sup>2</sup>	Cu16-300 mm <sup>2</sup>	-