



10105 TT

NF C20-130 Tulip copper cable lug

TT cable lug manufactured from electrolytic copper with a tinplated finish to improve electrical contact. The tulip shape at the end of the barrel favours the introduction of the cable.

Electric test according to CEI 61238-1 standard.

Code	Ref.	Section (mm ²)		Dimensions (mm)							Kg x 100	Bag	Box	€ x 100
				ØE	ØI	L	ØT	A	C1	L2				
009220	TT-6/5	6	5	5,5	3,3	30,50	5,3	13,0	8,0	11,0	0,243	100	1200	57,61
009230	TT-6/6	6	6			32,50	6,5		8,0		1000	57,61		
009270	TT-10/6	10	6	6,8	4,3	30,50	6,5	12,0	6,5	12,0	0,598	100	800	65,27
009280	TT-10/8		8			37,00	8,5		15,0		10,0	100	600	65,27
009320	TT-16/6	16	6	8,0	5,3	33,30	6,5	12,0	6,3	14,0	0,712	100	500	75,80
009330	TT-16/8		8			37,50	8,5		16,0		8,5	100	500	77,70
009360	TT-25/6	25	6	9,5	6,6	36,30	6,5	13,0	6,3	15,0	0,874	50	300	105,63
009370	TT-25/8		8			42,00	8,5		18,0		10,0	50	300	113,31
009380	TT-25/10	10	10	46,00	10,5	18,0	12,0	50	250	121,35				
009420	TT-35/8	35	8	11,0	7,9	44,00	8,5	17,0	10,0	17,0	1,591	50	200	152,68
009430	TT-35/10		10			49,00	10,5		17,0		12,0	50	200	167,74
009510	TT-50/8	50	8	12,5	9,2	47,00	8,5	18,0	10,0	19,0	2,109	20	140	209,58
009520	TT-50/10		10			52,00	10,5		18,0		12,0	20	140	224,69
009530	TT-50/12	12	12	54,00	13,0	13,0	13,0	20	120	216,72				
009570	TT-70/8	70	8	15,0	11,0	51,00	8,5	21,0	10,0	21,0	2,241	20	100	331,43
009580	TT-70/10		10			55,00	10,5		21,0		12,0	20	80	350,27
009590	TT-70/12	12	12	59,00	13,0	22,0	13,0	20	80	355,57				
009640	TT-95/10	95	10	17,0	13,1	60,00	10,5	25,0	12,0	22,0	4,518	20	60	455,83
009650	TT-95/12		12			62,00	13,0		13,0		20	60	455,83	
009660	TT-95/14	14	14	66,50	15,0	14,5	14,5	20	60	492,70				
009670	TT-95/16	16	16	70,00	17,0	16,0	16,0	20	60	492,70				
009710	TT-120/12	120	12	19,0	14,5	66,00	13,0	28,0	13,0	26,0	6,544	10	50	751,30
009720	TT-120/14		14			69,50	15,0		14,5		10	50	751,30	
009730	TT-120/16	16	16	72,00	17,0	16,0	16,0	10	50	751,30				
009760	TT-150/12	150	12	21,0	16,2	73,00	13,0	30,0	15,0	30,0	8,578	10	40	979,88
009770	TT-150/14		14			73,00	15,0		15,0		10	40	979,88	
009780	TT-150/16	16	16	75,00	17,0	16,0	16,0	10	40	979,88				
009810	TT-185/12	185	12	23,0	18,0	81,00	13,0	33,5	16,0	32,0	10,255	10	40	1.334,67
009830	TT-185/16		16			87,00	17,0		19,0		10	30	1.334,67	
009860	TT-240/12	240	12	26,0	20,6	93,50	13,0	38,0	21,5	35,0	14,383	5	25	1.601,08
009880	TT-240/16		16			93,50	17,0		21,5		5	25	1.601,08	
009920	TT-300/16	300	16	28,0	23,0	102,00	17,0	41,0	19,0	44,0	16,270	5	10	2.214,60
009950	TT-400/16	400	16	32,0	26,0	115,00	17,0	46,5	19,0	44,0	26,819	4	8	4.195,08